

IVFtech Light 0,6 and 1,2

IVFtech Light is a standard cabinet.

Options:

0,6m is available with one full heated area and preparation for microscope or as a cold cabinet.

IVFtech Light 0,6m is available with wheels, easy to move around for use in different locations.

Like all our other cabinets IVFtech Light can also be supplied with adjustable electrical stand or fixed stand.

Front opening: Fixed

Downflow: 0,25-0,40m/s

Energy consumption: 400W

HEPA filter EN 1822, H-14: 99.995 %MPPS
Prefilter, quality EU 3: ASHRAE 83
min/max height adjustable: 600-1000mm
min/max height fixed: 800-850mm

Temp. settings: Room temp. to 50°C

Air quality: Class A

Voltage-frequency: 120-60 / 230-50

Fuses: 10A

External dimensions: D500xW650xH975mm Internal dimensions: D495xW640XH460

Weight: 32kg Shipping volume net: 0,6m³





Options:

1,2m is available with one standard heated area and preparation for microscope or as a cold cabinet.

IVFtech Light 1,2m is available with a fixed stand.

Front opening: Fixed

Downflow: 0,25-0,40m/s

Energy consumption: 450W

HEPA filter EN 1822, H-14: 99.995 %MPPS

Prefilter, quality EU 3: ASHRAE 83

min/max height adjustable: N/A

min/max height fixed: 800-850mm

Temp. settings: Room temp. to 50°C

Air quality: Class A

Voltage-frequency: 120-60 / 230-50

Fuses: 10A

External dimensions: D635xW1240xH1050mm Internal dimensions: D600xW1230XH520mm

Weight: 139kg Shipping volume net: 1,5m³



IVFtech

Toppevadvej 34-38 DK - 3660 Stenløse

Phone + 45 39 40 25 65

Fax + 45 39 40 25 64

www.ivftech.dk

E-mail: info@ivftech.dk